MOTTA EnduroRide High Mileage 4T 25W-60

mineral four-stroke motocicleta aceite de motor para robust everyday service

SAE 25W-60

Descripción del producto

MOTTA EnduroRide High Mileage 4T 25W-60 is a mineral four-stroke motorcycle engine oil in SAE 25W-60. It is positioned within the MOTTA EnduroRide range para applications calling para API SG y JASO MA2 performance references, subject to the motocicleta manufacturer's viscosity y service recommendations.

Características y beneficios

Característica	Beneficio para el cliente
Multigrado viscosity profile	Supports aceite circulation at start-up y lubricating-film strength at operating temperatura.
mineral formulation	Supports engine limpieza, protección antidesgaste y consistent everyday operation.
JASO MA2 fricción design	Supports controlled wet-clutch engagement y shared engine/gearbox lubrication.
Shear-stable formulation approach	Helps maintain viscosity through motocicleta engine y transmission service.

aplicaciones

- High-mileage four-stroke motocicletas y motocicleta taxis operating in warm climates.
- Motores que requiere SAE 25W-60 y the stated API performance reference.
- Wet-clutch y common-sump sistemas que requiere JASO MA2 fricción performance.
- Use according to the fabricante del vehículo's aceite y service recommendations.

Performance Reference

API SG performance reference | JASO MA2 performance reference

These references describe the intended nivel de desempeño y No imply licensing, certification or formal third-party approval.

Propiedades típicas

Propiedad	Método de ensayo	Typical Valor
Cinemática Viscosidad @ 40°C	ASTM D445	196.7 cSt
Cinemática Viscosidad @ 100°C	ASTM D445	22.77 cSt
Viscosidad Índice	ASTM D2270	132
Punto de inflamación, COC	ASTM D92	260 °C
Punto de fluidez	ASTM D97	-31 °C

Traducción de la TDS en inglés. En caso de diferencia, prevalece la versión inglesa.

Envase y Disponibilidad

Envase Item	producto Information
Disponible Formatos de envase	Subject to order y sales confirmation.
Pack format	Factory-sealed packages supplied according to mercado y order.
producto identification	Labels identify producto name, grado de viscosidad y lote information.

Salud, Seguridad y Almacenamiento

Before Manejo, Almacenamiento, transportee or Eliminación, read the aplicable Seguridad Data Sheet (SDS). Store in a cool, dry y well-ventilated area. Keep original containers sealed, Evite la contaminación y maintain clear lote identification.

The Valores shown are typical technical characteristics y are not producto specifications. Normal productoion variation may occur. These Valores are not lote-specific inspection results y must not be used as Certificate de Analysis data. producto selection should follow the motocicleta manufacturer's viscosity, performance y service-interval recommendations.