MOTTA GT20

High-Temperature sintético grasa

NLGI 2

Descripción del producto

MOTTA GT high-temperatura synthetic greases combine synthetic base fluids con a heat-resistant thickener system para oven conveyors, kiln bearings, electric-motor bearings y other lubrication points exposed to high or wide temperatura cycles.

They provide mechanical stability, protección antidesgaste, rust y corrosion control y resistencia al agua; the correct variant must be selected para bearing speed, load, temperatura range y relubrication Método.

Características & Beneficios

Característica	Beneficio para el cliente
Mechanical stability	Maintains grasa consistency during mechanical working.
protección antidesgaste	Protects loaded bearings y contacting surfaces.
Corrosion resistance	Helps protect lubricated metal surfaces against rust y corrosion.
resistencia al agua	Helps the grasa remain effective when exposed to water or moisture.

aplicaciones

- Rolling-element y plain bearings que requiere the stated NLGI grade.
- grasa-lubricated joints, pins, bushes y general máquinary.
- Centralized or manual lubrication sistemas compatible con the selected consistency.

Siga siempre la recomendación del fabricante del equipo para el grado de viscosidad, nivel de desempeño y intervalo de servicio.

Performance References

Standard / Reference	Performance Reference
ISO 6743-9 / DIN 51502	Classified per ISO 6743-9 y DIN 51502 grease designation practice para the stated NLGI grade y thickener system.

Performance references indicate formulation target / nivel de desempeño y No constitute formal approval, certification or license unless explicitly stated.

Typical Characteristics

Propiedad	Método de ensayo	Typical Valor
NLGI Grade	-	2
Thickener Type	-	Clay (PAO base)
Color / Apariencia	Visual	Light brown
Worked Penetration @ 25°C, 0.1mm	ASTM D217	280
Dropping Point, °C	ASTM D2265	260

Traducción de la TDS en inglés. En caso de diferencia, prevalece la versión inglesa.

Propiedad	Método de ensayo	Typical Valor
Base aceite Viscosidad @ 40°C, cSt	ASTM D445	100

Envase

Envase Item	producto Information
Disponible Formatos de envase	Confirmado con the aplicable order documentación.
Formato de contenedor	Industrial Tambor y bulk formats; confirmed at order.
Disponibilidad	Envase presentation y artwork are confirmed con the aplicable order documentación.

Salud, Seguridad & Almacenamiento

For Salud, seguridad y medio ambienteal orientación, consulte the aplicable Seguridad Data Sheet antes de Manejo, Almacenamiento, transportee or Eliminación.

Store in tightly closed original containers in a cool, dry y well-ventilated area. Protect from direct sunlight, rain, excessive heat y contamination. Apply first-in, first-out stock rotation y keep lote identification traceable throughout the distribution chain.

Valores típicos Disclaimer

The Valores shown are typical technical characteristics y are not producto specifications. Normal productoion variation may occur. These Valores are not lote-specific inspection results y must not be used as Certificate de Analysis data.

Traducción de la TDS en inglés. En caso de diferencia, prevalece la versión inglesa.