MOTTA Q1000

High-TBN Gas aceite de motor

SAE 40

Descripción del producto

MOTTA Q1000 is a high performance natural gas engine oil para modern medium y high speed four-stroke engines burning fuels containing corrosive species such as hydrogen sulphide or halogens.

As a high-TBN gas aceite de motor, its alkalinity reserve neutralises corrosive attack, protecting cylinders, valve areas y bearings para long engine life y low maintenance cost.

Características & Beneficios

Característica	Beneficio para el cliente
Control de depósitos	Helps maintain piston, ring-belt y valve-area limpieza.
Oxidation y nitration control	Resists lubricante thickening y degradation in gas-engine service.
protección antidesgaste	Protects bearings y other lubricated engine componentes.
Corrosion control	Helps protect internal surfaces against corrosive combustion productos.

aplicaciones

- Stationary natural-gas or compatible gas-fuelled engines.
- Cogeneration y gas-compression installations.
- Motores que requiere the stated viscosity y the indicado producto performance profile.

Siga siempre la recomendación del fabricante del vehículo para el grado de viscosidad, nivel de desempeño y intervalo de servicio.

Performance References

Standard / Reference	Performance Reference
SAE J300 / low-ash gas engine oil practice	Formulated to low-ash stationary gas aceite de motor practice para four-stroke engines, compatible con catalytic converters.

Performance references indicate formulation target / nivel de desempeño y No constitute formal approval, certification or license unless explicitly stated.

Typical Characteristics

Propiedad	Método de ensayo	Typical Valor
SAE Grade	SAE J300	SAE 40
Cinemática Viscosidad @ 40°C, cSt	ASTM D445	130
Cinemática Viscosidad @ 100°C, cSt	ASTM D445	13.7
Viscosidad Índice	ASTM D2270	102
Punto de fluidez, °C	ASTM D97	-18
Punto de inflamación (COC), °C	ASTM D92	265
Densidad @ 15°C, kg/L	ASTM D4052	0.9

Traducción de la TDS en inglés. En caso de diferencia, prevalece la versión inglesa.

Propiedad	Método de ensayo	Typical Valor
Sulfated Ash, wt%	ASTM D874	1.1
TBN, mgKOH/g	ASTM D2896	8.5

Envase

Envase Item	producto Information
Disponible Formatos de envase	Confirmado con the aplicable order documentación.
Formato de contenedor	Industrial Tambor y bulk formats; confirmed at order.
Disponibilidad	Envase presentation y artwork are confirmed con the aplicable order documentación.

Salud, Seguridad & Almacenamiento

For Salud, seguridad y medio ambienteal orientación, consulte the aplicable Seguridad Data Sheet antes de Manejo, Almacenamiento, transportee or Eliminación.

Store in tightly closed original containers in a cool, dry y well-ventilated area. Protect from direct sunlight, rain, excessive heat y contamination. Apply first-in, first-out stock rotation y keep lote identification traceable throughout the distribution chain.

Valores típicos Disclaimer

The Valores shown are typical technical characteristics y are not producto specifications. Normal productoion variation may occur. These Valores are not lote-specific inspection results y must not be used as Certificate de Analysis data.

Traducción de la TDS en inglés. En caso de diferencia, prevalece la versión inglesa.