# MOTTA UltraTech Scooter 4T 5W-40

**Daily-service totalmente sintético four-stroke motocicleta aceite de motor**

SAE 5W-40

## Descripción del producto

MOTTA UltraTech Scooter 4T 5W-40 is a full synthetic four-stroke motorcycle engine oil in SAE 5W-40. It is positioned within the MOTTA UltraTech range para applications calling para API SN y JASO MA2 performance references, subject to the motocicleta manufacturer's viscosity y service recommendations.

## Características y beneficios

| Característica | Beneficio para el cliente |
|---|---|
| Multigrado viscosity profile | Supports aceite circulation at start-up y lubricating-film strength at operating temperatura. |
| Totalmente sintético formulation | Supports engine limpieza, protección antidesgaste y consistent everyday operation. |
| JASO MA2 fricción design | Supports controlled wet-clutch engagement y shared engine/gearbox lubrication. |
| Shear-stable formulation approach | Helps maintain viscosity through motocicleta engine y transmission service. |

## aplicaciones

- Four-stroke scooters or motocicletas que requiere SAE 5W-40.
- Wet-clutch sistemas que requiere JASO MA2 fricción performance.
- Urban commuting y intercity daily service.
- Use according to the fabricante del vehículo's aceite y service recommendations.

## Performance Reference

API SN performance reference | JASO MA2 performance reference

These references describe the intended nivel de desempeño y No imply licensing, certification or formal third-party approval.

## Propiedades típicas

| Propiedad | Método de ensayo | Typical Valor |
|---|---|---|
| Cinemática Viscosidad @ 40°C | ASTM D445 | 85 cSt |
| Cinemática Viscosidad @ 100°C | ASTM D445 | 13.95 cSt |
| Viscosidad Índice | ASTM D2270 | 170 |
| Punto de inflamación, COC | ASTM D92 | 214 °C |
| Punto de fluidez | ASTM D97 | -39 °C |
| Total Base Number | ASTM D2896 | 7 mg KOH/g |



Traducción de la TDS en inglés. En caso de diferencia, prevalece la versión inglesa.

## Envase y Disponibilidad

| Envase Item | producto Information |
|---|---|
| Disponible Formatos de envase | Subject to order y sales confirmation. |
| Pack format | Factory-sealed packages supplied according to mercado y order. |
| producto identification | Labels identify producto name, grado de viscosidad y lote information. |

## Salud, Seguridad y Almacenamiento

Before Manejo, Almacenamiento, transportee or Eliminación, read the aplicable Seguridad Data Sheet (SDS). Store in a cool, dry y well-ventilated area. Keep original containers sealed, Evite la contaminación y maintain clear lote identification.

The Valores shown are typical technical characteristics y are not producto specifications. Normal productoion variation may occur. These Valores are not lote-specific inspection results y must not be used as Certificate de Analysis data. producto selection should follow the motocicleta manufacturer's viscosity, performance y service-interval recommendations.