MOTTA VP100

Low-Volatility White-aceite Vacuum Pump lubricante
ISO VG 100

Descripción del producto

MOTTA VP100 is a vacuum-pump lubricant blended from low-volatility white oil para the lubrication, sealing y cooling de compatible aceite-sealed vacuum pumps.

Controlado volatility, estabilidad a la oxidación y aceite-film retention support vacuum performance, limit lubricante loss y protect pump bearings y sealing areas. Pump type, process gas, operating temperatura y contaminant exposure must be considered Antes del uso.

Características & Beneficios

Característica	Beneficio para el cliente
Vacuum sealing support	Maintains an aceite film between compatible pump componentes.
Controlado volatility	Helps limit lubricante loss under vacuum conditions.
Oxidation resistance	Helps control aceite degradation y deposits.
protección antidesgaste	Protects moving pump componentes during operation.

aplicaciones

- compatible rotary-vane y other aceite-sealed vacuum pumps.
- Vacuum sistemas que requiere the stated ISO viscosity grade.
- Processes compatible con mineral white-aceite vacuum-pump lubricante.

Siga siempre la recomendación del fabricante del equipo para el grado de viscosidad, nivel de desempeño y intervalo de servicio.

Performance References

Standard / Reference	Performance Reference
ISO 6743-3 DVC	Low-volatility vacuum pump aceite per ISO 6743-3 vacuum pump lubricant classification.

Performance references indicate formulation target / nivel de desempeño y No constitute formal approval, certification or license unless explicitly stated.

Typical Characteristics

Propiedad	Método de ensayo	Typical Valor
ISO Viscosidad Grade	ISO 3448	VG 100
Densidad, kg/L	DIN 12185	0.875
Cinemática Viscosidad @ 40°C, cSt	DIN 3104	100
Punto de inflamación (PM), °C	DIN 2719	270
Punto de fluidez, °C	-	-8

Traducción de la TDS en inglés. En caso de diferencia, prevalece la versión inglesa.

Envase

Envase Item	producto Information
Disponible Formatos de envase	Confirmado con the aplicable order documentación.
Formato de contenedor	Industrial Tambor y bulk formats; confirmed at order.
Disponibilidad	Envase presentation y artwork are confirmed con the aplicable order documentación.

Salud, Seguridad & Almacenamiento

For Salud, seguridad y medio ambienteal orientación, consulte the aplicable Seguridad Data Sheet antes de Manejo, Almacenamiento, transportee or Eliminación.

Store in tightly closed original containers in a cool, dry y well-ventilated area. Protect from direct sunlight, rain, excessive heat y contamination. Apply first-in, first-out stock rotation y keep lote identification traceable throughout the distribution chain.

Valores típicos Disclaimer

The Valores shown are typical technical characteristics y are not producto specifications. Normal productoion variation may occur. These Valores are not lote-specific inspection results y must not be used as Certificate de Analysis data.

Traducción de la TDS en inglés. En caso de diferencia, prevalece la versión inglesa.